

# WDR DOME CAMERA

MXC-DP300WDR



**Professional**

## OVERVIEW

MAXCOM employs the latest 4th Generation Digital Pixim technology in their range of WDR Cameras. Designed for applications where High Definition facial recognition is required under extreme dynamic lighting condition, strong light reflections and where intensity of illumination can vary excessively. WDR enables the capture and display of both bright areas and dark areas in the same frame, delivering a very high quality, supreme resolution and very accurate image. As each pixel acts as a camera, the picture taken by one pixel does not affect the picture quality captured by other pixels. This camera is incredibly flexible to install with its 3-axis camera construction.

## SPECIFICATIONS

CCD Sensor	1/3" Pixim Digital Pixel System
Resolution	690 TVL
Min. Illumination	0.1 Lux
Wide Dynamic Range	120dB
SDNR	Yes
Viewing Angle	28° ~ 136° (2.8~12mm)
AGC, Contrast, Sharpness	Selectable via OSD
Motion, Privacy, Mirror	Selectable via OSD
Camera, ID, Shutter, WBL, BLC	Selectable via OSD
Reverse Polarity Protection	Yes
S/N Ratio	52dB
Iris Mode	Auto Iris Vari-focal (IR Corrected)
Communication	RS-485(Pelco-D)
Mounting	Ceiling / Wall / Slope
Dimension	130.8 x 96 mm
Weight	400g
Power Source	Regulated 12V DC or 24V AC



**DIGITAL  
PIXEL<sup>®</sup>  
SYSTEM**  
FROM PIXIM



CCD

PIXIM